

# **Innovative Erosion Control Technology In Florida**

**Paden E. Woodruff**

**Bureau of Beaches and Coastal Systems  
Florida Department of Environmental  
Protection**



**Greatest cause of erosion is improved inlets**

# Second cause is storm damage

North Captiva Island, FL  
September 29, 1999



August 15, 2004



# Third cause is construction of structures



# **Early Experiences**

**Before 1989, no organized program to evaluate innovative technologies**

**No performance criteria**

**No test plan**

**Therefore, insufficient data to assess performance or effectiveness**

# **Section 27 of Laws of Florida 89-175**

**Legislative intent to encourage  
development of new and innovative  
methods for dealing with erosion  
problems**

# **Rule 62B-41.0075**

## **Florida Administrative Code**

### **“Experimental Coastal Construction”**

**Rule requires a “test plan” with specific criteria to evaluate performance**

# **Early 1980's: Artificial Seaweed**

## **Problems included:**

- Inadequate anchoring system**
- Individual fronds would lose buoyancy**
- Unknown environmental impact**

# Artificial Seaweed

1983	100' to 300' south of R-90, Collier Co.	Synthetic strips 2" wide X 5' long anchored w/ a sand filled tube. 8 rows, 500' long each.	Analysis of comparative profiles indicated the project was ineffective. Department recommended removal. Diver inspection revealed the fronds were either buried, washed away or removed.
1984	100' to 300' south of T-15, Manatee Co.	A grid was located 210' seaward of the mean high-water line. Grid consisted of 4 interlocking sandbag tubes with 4 rows of seaweed fronds.	Monitoring required as a permit condition was not conducted, a removal order was issued by the Department, and the project removed. Department conclusion was the project was ineffective.
1984	500' N of T-203 to 300' N of T-204, Highland Beach, Palm Beach Co.	5 rows of seaweed, 10' apart approx. 1200' long were located approx. 300' seaward of mean high-water	The 6 mo. report indicated 65% of the project ineffective, and no further monitoring was completed. A 1992 inspection showed no trace of project.

# Artificial Seaweed Theory



# Artificial Seaweed in Reality



# **“Net Groins”**

**Department has permitted, and in some cases, cost-shared, in projects referred to as “net groins”**

# Net Groins


1986	150' N to 350' S of R-90, Collier Co.	Flexible netting at 50' to 100' intervals for 700'. Located from mean high-water to 50' seaward.	Project was never constructed.
1987	130' to 630' S of R-71, Collier Co.	Nets at 50' to 100' intervals for 500'. Located from mean high-water to 50' seaward.	Definitive conclusions on performance cannot be drawn due to the experiments' short duration, magnitude, location and insufficient monitoring.
1997	400' W to 800' E of R-169, Dog Island, Franklin Co.	Nylon net groins of various mesh size extended 150' seaward from mean high-water at 150-200' intervals. Stanchion system to raise nets as sediment accumulates.	Project not installed.

2000	2 locations on Eglin Air Force Base, Okaloosa Co.	Netting on stanchions from upper beach to -3 ft.	3 <sup>rd</sup> party review: minimal effect on shorelines
2001	Naples, Collier Co. R 76-79	Netting spread 100 ft. for 3,000 ft.	3 <sup>rd</sup> party review: minimal accretion in groin field; significant loss in adjacent areas
2005	Inlet Beach, Walton Co.	14 groins 150 ft. apart	3 <sup>rd</sup> party review: Success criteria not met

# Net Groins

TYPICAL ELEVATION - POROUS GROYNE SYSTEM

PERMIT NO.











# DANGER

Beach Reclamation Project  
Underwater and above water  
mesh and stanchions.



- Stay at least 25 feet away from the project area.
- Do not run, walk, surf, swim, boat, or jet-ski within 25 feet of the mesh and stanchions.
- Collision with the stanchion may cause death or serious injury.
- Entanglement or entrapment in the mesh may cause death or serious injury.

**Other types of beach erosion control can be referred to as “beach manipulation”**

# **Beach Scraping**

**Usually conducted following storm events to accelerate natural recovery.**

**Can have adverse impact on the beach and dune system**

**Department has developed guidelines for permitting to minimize potential adverse impacts.**

# **Beach Dewatering**

**Lowers the water table beneath the beach and in theory reduces fluidization of material. This effect reduces sediment suspension in the swash zone.**


# Beach Manipulation


<b>Beach Builder Screws</b>	<b>1985</b>	<b>50' S R-27 Flagler Co.</b>	<b>2 auger screws (40' sections) laid from MHW seaward of MLW</b>	<b>Project was ineffective at moving material and was discontinued</b>
<b>Beach Scraping</b>	<b>1985</b>	<b>R-29 to R-46 City of Cocoa Beach, Brevard Co.</b>	<b>Scraping of 3 mi. of beach from MLW to MHW with placement at toe of escarpment.</b>	<b>Monitoring was inconclusive. Small quantity of material and inadequate spacing of profiles</b>
<b>Beach Scraping</b>	<b>2004</b>	<b>Walton Co., City of Destin, Okaloosa Co.</b>	<b>MLW to MHW, placement at toe of escarpment</b>	

# Beach Manipulation

<b>Beach Dewatering</b>	<b>1988</b>	<b>297'S to 280' N of R36, Sailfish Point, Martin Co.</b>	<b>Submersible pump and piping system beneath beach</b>	<b>Inadequate information to determine natural vs. system induced change. Beach was stable</b>
-----------------------------	-------------	---	---	--

# Beach Dewatering





# Physical Structures

**Various types of physical structures have been tried, and continue to be permitted and funded, including a variety of sand filled geotextile structures in various configurations.**

# Physical Structures

Protect Tube II	1989	190' to 920' S of T-15, Longboat Key, Sarasota Co.	3-celled, sand-filled geotextile tube structure w/ crest elevation +6.5 ft. NGVD. 15 ft. wide, 600' were placed as emergency work in 1988, and a 125' added and monitored.	Beach remained stable during 2 yr. monitoring period, and no downdrift problems noted. Unusually calm period. Inhibition of turtle nesting remains a concern.
Longard Tubes	1992	350' N of R-59 to R-60, Sand Key, Sarasota Co.	70" and 40" diameter sand-filled tubes arranged as groins connecting to an offshore sill. Groin compartments filled w/ 99,000 cyd of sand.	Project performed well. Tubes were damaged and settlement occurred. Area now has a restoration project.
Undercurrent Stabilizers	1984	92' to 742' S of R-96, Captiva Island, Lee Co.	Groins constructed using 2, side by side, sand-filled bags, 13' X 5', and underlaid by anchored filter fabric.	Consultants and department concluded no beneficial effect and no improved sediment accretion rates.

# Longard Tube Installation



SAND KEY

1993

# **Proprietary Reef Structures**


**Another class of physical structures**

**Also known as**

**“thin-line submerged breakwaters”**

**A submerged breakwater modifies both the wave and current fields landward of the breakwater, with modification depending substantially on the crest elevation relative to the still water level.**

# Proprietary Reef Structures




P.E.P. Reef

Proprietor : American Coastal  
Engineering, Inc.

Weight/foot : 4167 lb/ft

Installation Locations :  
Palm Beach, Fl.




Beachsaver

Proprietor : Breakwaters  
International, Inc.

Weight/foot : 4200 lb/ft

Installation Locations :  
Sea Isle City, N.J.,  
Avalon, N.J.




Beach Beam

Proprietor : Advanced Erosion  
Control, Inc.

Weight/foot : 2000 lb/ft

Installation Locations :  
Maryland




Beach Prism

Proprietor : Beach Prisms, Inc.

Weight/foot : 1232 lb/ft

Installation Locations :  
Bennetts Point, Md.



Campbell Module

Proprietor : Campbell Module


Weight/foot : 3500 lb/ft

Installation Locations :  
Sea Island, Ga.

# Midtown Beach Prefabricated Erosion Prevention (P.E.P.) Reef


- 57 units installed June of 1992
- Additional 273 in 1993
- 4,176 ft. long, 6 ft. high, at -9.5 NGVD
- Purpose was to reduce wave heights and to accumulate sand in it's lee.
- Natural reef 700 ft. seaward


# PEP Reef





# PEP Reef Over Time















**Figure 12** Average Sea Floor Elevation History and Changes in Average Elevations for Scour Rod Numbers 14 through 19

# Changes Over Time



# Landward Volumetric Changes




Figure 32 Histories of Cumulative Volume Changes for Three Inner Zones.

# Seaward Volumetric Change




Figure 33 Histories of Cumulative Volume Changes for Three Outer Zones.

**23 months following installation, the Town of Palm Beach elected to remove the PEP reef and construct a beach restoration project. The PEP reef units were used to construct a groin field within the project area.**

# **Vero Beach Prefabricated Erosion Prevention Reef (P.E.P.)**

- **Installed August 1996**
- **3,000 ft. long, 250 ft. seaward, -7 to -9  
NGVD**
- **Environmentally sensitive area**
- **Purpose to reduce wave height, stabilize  
shoreline and volumetric changes, and  
reduce storm wave energy.**






Figure 2. Location of the City of Vero Beach with location of the P.E.P. Reef.

# PEP Reef Installation





**LEGEND**


- Scour Rod
- ⊙ Wave gage

*Atlantic Ocean*

Humiston Park

0 200 400  
SCALE (FT)

St.4  
St.5



**The monitoring program indicated minimal effect on shoreline. Indian River County is now pursuing a beach restoration project.**

**Workshop on Innovative Shore  
Protection Technology  
February 22-23, 2006  
Tallahassee, FL**

**Moderated by an independent coastal  
engineer from North Carolina**

# **PURPOSE**

**Explain Regulatory Process**


**Explain Funding Opportunities**

**Include Other State and Federal  
Agencies**


**Review Innovative Presentations**

# **New Dewatering System**

# PEM Function dewatering the beach



# **New Structures**



# SEAMOD Variable Sizes




- **Built on ideas from NavSea for the modular building of ships**
- **Same idea – precast concrete modules**
- **More cost effective than steel**
- **Easier to construct than steel**
- **Greater durability than steel**
- **Less maintenance**




# Subsurface Dune Protection Systems


## ProTecTube™ II & III Comparison



Water & sand “inflatable” Emergency Response Device

# SEABOX™ Deployment





©Beach Restoration, Inc.  
2005

Lebanon Tennessee ♦ St. Augustine  
Florida ♦ North Port Florida  
Baton Rouge Louisiana ♦ Galveston  
Texas ♦ Quebec Canada

# **New Mitigation Solutions**

# Multi-Purpose Reefs



## Coastal Protection

- Surfing
- Diving

## *Multi-use aspects*




*A technology inspired by Nature*



- Swimming

- Windsurfing

- Fishing



Nature's way. Offshore reefs naturally protect the coast



## ***Reef Ball™ Units***



# **Where Do We Go From Here?**

**More Scientifically Based Approach to Investigate Innovative Technologies...**

- Numerical & physical modeling**
- Peer review & analysis**
- Use of experimental test plan**

# **Where Do We Go From Here?**

## **Develop Innovative Applications Using Conventional Technologies.....**

- Structures to improve beach restoration project performance**
- Different construction technologies to reduce environmental concerns**
- Construction design to improve project performance and reduce environmental impact.**

# **Where Do We Go From Here?**

## **New Dredging Systems.....**

- **More efficient dredging vessels and deep water systems**
- **Separation technology such as the hydrocyclone to utilize marginal material**
- **Improve quality control**

# The End

